



Double Chamber Machines DK 400 and DK 600

Vacuum-Packing-Machines

LC and LS Features

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- Vacuum detection (no Tome Controls)
- Constructed for easy service work
- Automatic process with lid opening
- Extra-clean design of components such as sealing bar, counter bar, hinges
- Soft Air reventilation of the chamber
- Acrylic glas lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Oil-regeneration program

Additional LS Features

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



DK 600 LS



Control panel LC

Technical Data		DK 400 / DK 600	Technical Data		DK 400	DK 600	
■ Chamber size	height	210 mm / 210 mm	■ Weight	210 kg		240 kg	
	depth	470 (570*) / 610 mm		■ Length of sealing bar	2 x 460 mm		2 x 600 mm
	width	470 mm / 605 mm			or 4 x 460 mm		or 4 x 600 mm
■ External dimensions	height	970 mm / 970 mm	■ Packaging performance	1-2 / min.			
	depth	660 mm / 805 mm		■ Vacuum pump standard	40 m³ / h		63 m³ / h
	width	1.110 mm / 1.390 mm					
■ Electrical supply standard		400V/ 3					

Technical modifications reserved