



Table-Top-Model EST 15 Series

Vacuum-Packing-Machines

LC and LS Features

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- Easy removable sealing bar
- Constructed for easy service work
- Automatic process with lid opening
- Extra-clean design of components such as sealing bar, counter bar, hinges
- Soft Air reventilation of the chamber
- Acrylic glas lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Vacuum detection (no Time Controls)
- Oil-regeneration program

Additional LS Features

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



Tabel-Top-Model: EST 15 LC



Tabel-Top-Model: EST 15 LS

Technical Data		EST 15
■ Chamber size inside	height	115 mm
	depth	405 mm
	width	305 mm
■ External dimensions	height	345 mm
	depth	586 mm
	width	365 mm
■ Weight		49 kg
■ Length of sealing bar		300 mm
■ Packaging performance		ca. 2/ min.
■ Vacuum pump standard		16 m ³ / h
■ Electrical supply standard		230V / 1 or on request

Technical modifications reserved