



## Standmodel **EST 40 Series**

Vakuum-Verpackungs-Maschinen

### LC and LS Features

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- Easy removable sealing bar
- Constructed for easy service work
- Automatic process with lid opening
- Oil-regeneration program
- Extra-clean design of components such as sealing bar, counter bar, hinges
- Soft Air reventilation of the chamber
- Acrylic glas lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Vacuum detection (no Time Controls)

### Additional LS Features

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



Control Panel LC

Technical Data		EST 40
■ Chamber size inside	height depth Width	210 mm 470 (570*) mm 470 mm
■ External dimensions	height depth width	970 mm 660 mm 530 mm
■ Weight		95 kg
■ Length of sealing-bars		1 x 460 mm or 2 x 455 mm
■ Packaging performance		1 bis 3 / min.
■ Vacuum pump standard		40 m <sup>3</sup> / h
■ Electrical supply standard	LS: 400V/ 3 or on request	
* Chamber extension in the middle at 100 depth		

EST 40 LS