



Table-Top-Model **EST 40 T**

Vacuum-Packing-Machines

LC and LS Features

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- Easy removable sealing bar
- Constructed for easy service work
- Automatic process with lid opening
- Extra-clean design of components such as sealing bar, counter bar, hinges
- Soft Air reventilation of the chamber
- Acrylic glas lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Vacuum detection (no Time Controls)
- Oil-regeneration program

Additional LS Features

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



Control panel LC



EST 40 TLS

Technical Data	EST 40 T
■ Chamber size inside	height 200 mm depth 470 (570*) mm width 470 mm
■ External dimensions	height 450 mm depth 580 mm width 535 mm
■ Weight	85 kg
■ Length of sealing bar	460 mm or 2 x 455 mm
■ Packaging performance	1 to 2 / min.
■ Vacuum pump standard	21 m ³ / h
■ Electrical supply standard	LC: 230V / 1 or on request LS: 400V / 3 or on request
* Chamber extension in the middle at 100 mm depth Technical modifications reserved	