



## Standmodel **EST 60 Series**

### Vacuum-Packing-Machines

#### LC and LS Features

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- Easy removable sealing bar
- Constructed for easy service work
- Automatic process with lid opening
- Extra-clean design of components such as sealing bar, counter bar, hinges
- Soft Air reventilation of the chamber
- Acrylic glass lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Vacuum detection (no Time Controls)
- Oil-regeneration program

#### Additional LS Features

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



Control panel LC

Technical Data		EST 60
■ Chamber size inside	height	210 mm
	depth	610 mm
	width	605 mm
■ External dimensions	height	970 mm
	depth	805 mm
	width	670 mm
■ Weight		ca. 145 kg
■ Length of sealing bar		1 or 2 x 600 mm
■ Packaging performance		1 to 3 / min.
■ Vacuum pump standard		63 m <sup>3</sup> / h
■ Electrical supply standard		400V/ 3 or on request

Technical modifications reserved

EST 60 LS